



Trumbull®

TRULO® LO ODOR Low-Odor Asphalt

OPTIMUM PERFORMANCE—WITHOUT THE ODOR.

TruLo® Lo Odor asphalt. It takes most of the odor out of every hot asphalt job.

THE SWEET SMELL OF INNOVATION.

Owens Corning uses a patent technology specifically formulated to neutralize asphalt odor without impacting asphalt performance.

Testing shows:

- A 50% odor reduction in *TruLo* Lo Odor asphalt as compared to Trumbull® standard asphalt
- When compared to leading competitive low-odor asphalts and additives, *TruLo* Lo Odor asphalt was 45% more effective at reducing odor-causing compounds

NOW ODOR DOESN'T HAVE TO DICTATE SCHEDULING.

Many customers are understandably bothered by the odor of typical built-up roofing. *TruLo* Lo Odor asphalt:

- Helps you avoid costly night and weekend work scheduling due to odor issues
- Was developed to allow BURA to be used for even the most odor-sensitive sites, such as schools, restaurants and hospitals
- Reduces odor complaints

KEEP YOUR KETTLE ROUTINE.

TruLo Lo Odor asphalt follows the same kettle processing as standard asphalt—there is no messy, dangerous mixing of additives.

- Works effectively to control odor both on the roof and at the kettle
- Available at distributor locations nationwide
- Call 1-800-GET-PINK® for the distributor nearest you



TYPICAL PHYSICAL CHARACTERISTICS FOR TRULO® LO ODOR*

	TYPE I** Min. Max.		TYPE II** Min. Max.		TYPE III Min. Max.		TYPE IV Min. Max.	
Softening Point (°F)	140	150	165	175	195	205	215	225
Penetration Units: @ 77°F	20	35	20	30	17	24	15	22
Flash Point (°F)								
minimum	525		525		525		525	
typical†	550		550		550		550	
Ductility @ 77°F (cm)	13		4.0		3.0		2.0	
Solubility in Trichloroethylene %	99.8		99.8		99.8		99.8	
Typical Application Temperature for Hand Mopping EVT @ 125 CPS ± 25°F ^{††}	350		375		430		450	
For Machine Spreader EVT @ 75 CPS ± 25°F ^{††}	370		395		455		475	

* Meets or exceeds all ASTM D 312 requirements.

** Available by special order only.

† Check the Owens Corning Web site for regional differences in typical flash points.

†† Trumbull® asphalt typically has EVTs in the following range for this product. For specific EVTs for a product from a particular Trumbull Plant, check our Web site at www.trumbullasphalt.com or call 1-800-GET-PINK®.



**OWENS CORNING
ROOFING AND ASPHALT, LLC**
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10009927-B. Printed in U.S.A., June 2013 The color PINK is a registered trademark of Owens Corning. All Rights Reserved. ©2013 Owens Corning. All Rights Reserved.